



2018 HONDA GL1800 GOLD WING SPECIFICATIONS

Model	Gold Wing Tour	Gold Wing Tour DCT	Gold Wing Tour Airbag DCT	Gold Wing	Gold Wing DCT
ENGINE					
Type	1,833cc horizontally opposed six-cylinder four-stroke				
Valve Train	Single overhead Unicam® w/ 4 valves per cylinder, finger-follower rocker arm on intake, roller-rocker arm on exhaust				
Bore x Stroke	73mm x 73mm				
Compression Ratio	10.5:1				
Induction	Single throttle w/ 50mm bore, Throttle By Wire (TBW)				
Ignition	Full transistorized ignition				
Starter	Electric w/ Integrated Starter Generator system (ISG)				
Transmission	6-speed manual w/ Reverse	7-speed automatic DCT w/ Walking Mode F/R		6-speed manual	7-speed automatic DCT w/ Walking Mode F/R
Clutch	Multi-plate wet clutch	(2) multi-plate wet clutches		Multi-plate wet clutch	(2) multi-plate wet clutches
Final Drive	Shaft				
SUSPENSION					
Front	Double-wishbone front-suspension system w/ Showa shock absorber, 4.3 in. travel				
Rear	Pro-Link® system w/ Showa shock absorber, 4.1 in. travel				
BRAKES					
Front	(2) radially mounted 6-piston Nissin calipers w/ 320mm rotors, electronically controlled combined ABS				
Rear	(1) 3-piston Nissin caliper w/ 316mm rotor, electronically controlled combined ABS				
TIRES					
Front	130/70-18				
Rear	200/55-R16				
MEASUREMENTS					
Rake (Caster Angle)	30.5°				
Trail	109mm				
Length	101.4 in.			97.4 in.	
Width	36.4 in.	35.6 in.		36.4 in.	35.6 in.
Height	56.3 in. low windscreen; 61.2 in. high windscreen			52.8 in. low windscreen; 56.9 in. high windscreen	
Seat Height	29.3 in.				
Ground Clearance	5.1 in.				
Wheelbase	66.7 in.				
Fuel Capacity	5.5 gal.				
Color	Candy Ardent Red, Pearl White, Pearl Hawkseye Blue		Candy Ardent Red/Black	Candy Ardent Red, Matte Majestic Silver, Pearl Stallion Brown	
Curb Weight*	833 lbs.		842 lbs.	787 lbs.	800 lbs.

*Includes all standard equipment, required fluids and full tank of fuel—ready to ride

Meets current EPA standards

Models sold in California meet current CARB standards and may differ slightly due to emissions equipment

All specifications subject to change